

# Noxudol 750 Spray

## Thin ML-oil for interior treatment

### General

Noxudol 750 spray is a chemically active anti-corrosive compound with low surface tension, based on mineral oil, waxes, rust inhibitors and solvents. After drying it forms a waxy, moisture repellent surface. Because of the low surface tension it possesses good penetrating ability as well as the displacement of any moisture that may be present.

### Range of application

Noxudol 750 spray is a thin penetrating anti-corrosive that is intended for the treatment of the hollow spaces of motor vehicles according to the ML-method. In addition it may also be used for protection of iron and steel plates, beams, reserve parts, wire etc.

### Instructions for use

Start by cleaning the surface carefully, preferably with high pressure wash. Make sure the surface is dry before application. Shake the tin for about one minute. Build up the rust protection by means of several thin sprayings. After use the tin must be emptied in an upside-down position until pure propellant gas escapes.

### Package

30300095 / 500 ml spray (12 / pack)

### Technical data

Color:	Light brown
Consistency:	Liquid
Type of film:	Waxy
Density at 20° C	830 ± 20 kg/m <sup>3</sup>
Dry content:	50 ± 2 %
Solvents:	White spirit
Film thickness:	40 – 80 um
Temperatur vid applicering:	15 - 25° C
Avtvättbar med:	Renox Milieu or white spirit
Lagringstid:	24 months
Lagringsförhållanden:	5 - 35° C

**For further information we recommend the safety data sheet or instruction on package**

Issue: 2016-07-10



Auson AB, Kungälv, Sweden  
T: +46 (0)300-56 20 00  
www.auson.se

These information are for guidance only and are given without obligation. If there is some confusion we recommend that you do your own tests and ask for advice in writing from us.

**Noxudol**